





MICRO TRACK 48V BINARIO INCASSO / MICRO TRACK 48V FOR BUIL-IN APPLICATION

MICRO TRACK 48V BINARIO INCASSO

Alluminio, PVC, rame
Driver: escluso





Aluminum, PVC, copper
Driver: excluded

Articolo Item	Finitura Finish	IP	Lunghezza Lenght
4024-1	-NE 	IP20	1000
4024-2	-NE 	IP20	2000
4024-3	-NE 	IP20	3000

Accessori / Accessories

1 tappo chiuso + viti
N° 1 end cup + screws


Articolo Item	Finitura Finish
4024-T	-NE 



Schermo Opalino
Opaline filter

4024-3-OP


-OP



Cover di chiusura estetica
Closing cover

4024-C-3

-NE





MICRO TRACK 48V CONNESSIONI





Policarbonato, lega di rame
Driver: escluso
Corrente e tensione nominale

Polycarbonate, copper
 Driver: excluded
 Rated current and voltage

	Articolo Item	Finitura Finish	IP
Testata di alimentazione Head-feed	4023-A1	-NE	IP20



Testata di alimentazione a scomparsa con cavo L. 2500mm Foldway head-feed with cable length 2500mm	4023-A2	-NE	IP20
---	----------------	------------	------



Giunto passante


4023-GA

-NE



IP20

Through joint



Giunto a L


4023-GL1

-NE



IP20

L-shaped joint



Giunto a L Soffitto-Parete


4023-GL2

-NE



IP20

L-shaped joint for ceiling-wall application



Giunto Flessibile
Flexible joint

4023-GF

-NE 

IP20

