


# BEAM MASTER Ø25




**Alluminio**  
**Fascio di luce orientabile**  
**Driver: escluso**

Aluminum  
 Light beam: adjustable  
 Driver: excluded



## Corpo (ghiera esclusa) / Body (ring excluded)

	M 2700K	W 3000K	N 4000K
<b>4310</b>			
<b>Potenza/ Power</b>	1x 4W	1x 4W	1x 4W
<b>Lumen</b>	1x 380 lm	1x 410 lm	1x 410 lm
<b>CRI</b>	>90	>90	>90
<b>Alimentazione/ Supply</b>	24Vdc	24Vdc	24Vdc



Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
<b>4310</b>	<b>M</b>	<b>16</b>	<b>-BO</b>
	<b>W</b>		<b>-BV</b>
	<b>N</b>		<b>-NO</b>
			<b>-OR</b>
			<b>-RR</b>
			<b>-TI</b>

## Ghiera / Ring

Filtro anti-abbagliamento incluso  
 Antiglare filter included



Articolo Item	Finitura Finish
<b>410</b>	<b>-BO</b>
	<b>-BV</b>
	<b>-NO</b>
	<b>-OR</b>
	<b>-RR</b>
	<b>-TI</b>

## Alimentatori 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	N° art. alimentabili N° of items powerable	Dimmer
<b>1A0150</b>	30W MAX	IP20	160x58x18	1-4	-
<b>1A0151</b>	50W MAX	IP20	160x58x18	1-6	-
<b>1A0152</b>	75W MAX	IP20	160x58x18	1-9	-
<b>1A0145</b>	100W MAX	IP67	190x52x33	1-12	-
<b>1A0153</b>	150W MAX	IP20	240x60x49	1-18	-

## Centraline dimmerabili in remoto / Remote dimmable controllers

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmer
<b>1A0837</b>	144W MAX	IP20	132x22x19	1-10V   DALI   PUSH
<b>1A0838</b>	288W MAX	IP20	150x38x25	0-10V   1-10V   DALI   PUSH
<b>1A0172</b>	240W MAX	IP20	57x43x19	CASAMBI   PUSH

Controller 1 canale - DC

Controller 1 channel - DC