


MAXI DOT SPOT




Alluminio, vetro
Fascio di luce orientabile
Driver: escluso

Aluminum , glass
 Light beam: adjustable
 Driver: excluded

117	M 2700K	W 3000K	N 4000K	RGBW RGB+3000K
Potenza/ Power	1x 8,7W	1x 8,7W	1x 8,7W	1x 7,9W
Lumen	1x 1009 lm	1x 1052 lm	1x 1087 lm	1x 465lm
CRI	>90	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc	24Vdc



Articolo Item	Temperatura Temperature	°Ottica °Optic	Finitura Finish
117	M	00	-AA
	W	12	-BA
	N	35	-NA
		55	



117	RGBW	24	-AA
		36	-BA
		60	-NA

La versione RGBW necessita dell'Alimentatore in 24Vdc in tensione + la Centralina RGBW.

RGBW version requires constant voltage driver 24Vdc + driver RGBW


Alimentatori 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc


Articolo Item	Potenza Power	IP	Dimensioni Dimensions	N° art. alimentabili N° of items powerable	Dimmer
1A0143	14W MAX	IP67	90x39x19	1	-
1A0148	30W MAX	IP67	175x42x34	1-2	-
1A0149	75W MAX	IP67	200x50x32	1-4	-
1A0147	240W MAX	IP67	244x68x39	1-18	-





Controller per versione RGBW / Controller for RGBW version

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	N° art. alimentabili N° of items powerable	Dimmer
2A4314	67W MAX	IP20	90x71x58	1-7	DALI
2A4315	67W MAX	IP20	90x71x58	1-7	DMX
2A6165	67W MAX	IP20	90x71x58	1-7	PUSH

Accessori / Accessories

Articolo Item	Finitura Finish
Ghiera con visiera anti-abbagliamento Ring with antiglare visor 512	-NA 



Ghiera con filtro colorato Ring with colour filter 514	-AM 	-NA 
	-CY 	-NA 

Kit per fissaggio su albero Tree fixing kit 515
--

Picchetto Inox
Stainless steel peg

PC

