

INDOOR


SOSPENSIONE / SUSPENSION

CURUBA




- alluminio, vetro soffiato a bocca
- colore cavo: nero
- con cavo 5m: + 53€

- aluminum, mouthblown glass
- cable color: black
- with 5-meters cable: + 53€



Con rosone e driver / With canopy and driver

2603	M 2700K	W 3000K
Potenza/ Power	1x15.0W, 1x4.2W	1x15.0W, 1x4.2W
Nominal lumen	1x2720lm, 1x727lm	1x2760lm, 1x727lm
CRI	>90	>90
Alimentazione/ Supply	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
2603	M	-BO	-BO	-VBI
composed by	W	-NO	-NO	-VBL
RS04/02 (1Pz)		-BV	-BV	-VTM
2612 (1Pz)		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BBI
				-BBL
				-BTM
				-BAM
				-BFU
				-BVF



Con rosone e driver / With canopy and driver

2602	M 2700K	W 3000K
Potenza/ Power	1x15.0W, 1x4.2W	1x15.0W, 1x4.2W
Nominal lumen	1x2720lm, 1x727lm	1x2760lm, 1x727lm
CRI	>90	>90
Alimentazione/ Supply	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
2602 composed by RS04/O3 (1Pz) 2612 (1Pz)	M	-BO	-BO	-VBI
	W	-NO	-NO	-VBL
		-BV	-BV	-VTM
		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BBI
				-BBL
				-BTM
				-BAM
				-BFU
				-BVF



Solo corpo / Body only

2612	M 2700K	W 3000K
Potenza/ Power	1x15.0W, 1x4.2W	1x15.0W, 1x4.2W
Nominal lumen	1x2720lm, 1x727lm	1x2760lm, 1x727lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA




Articolo Item	Temperatura Temperature	Corpo Body	Vetro Glass
2612	M	-BO	-VBI
	W	-NO	-VBL
		-BV	-VTM
		-OR	-VAM
		-RR	-VRS
		-TI	-VFU
		-VF	-VVF
			-BBI
			-BBL
			-BTM
			-BAM
			-BFU
			-BVF

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver

Solo corpo con cavo 5m / Body only with 5m cable


2612/01	M 2700K	W 3000K
Potenza/ Power	1x15.0W, 1x4.2W	1x15.0W, 1x4.2W
Nominal lumen	1x2720lm, 1x727lm	1x2760lm, 1x727lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA



Articolo Item	Temperatura Temperature	Corpo Body	Vetro Glass
2612/01	M	-BO	-VBI
	W	-NO	-VBL
		-BV	-VTM
		-OR	-VAM
		-RR	-VRS
		-TI	-VFU
		-VF	-VVF
			-BBI
			-BBL
			-BTM
			-BAM
			-BFU
			-BVF

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver

Convertitore da 48Vdc a 500mA / 48Vdc to 500 mA converter



Articolo Item	art. alimentabili items powerable
2A7900	1

Necessita di driver remoto a 48Vdc
Requires 48V remote driver

Driver 48Vdc in tensione in remoto / Remote constant voltage drivers 48Vdc




Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0633	1-2	70W	IP20	210x45x49	ON-OFF
1A0634	1-4	150W	IP20	210x45x49	ON-OFF
1A1239	1-6	240W	IP67	244x68x39	ON-OFF
1A2493	1-8	320W	IP67	252x90x44	ON-OFF

Centraline dimmerabili in remoto / Remote dimmable controllers



Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0837/48	288W	IP20	132x22x20	PUSH DALI 1-10V
1A0838/48	576W	IP20	164x38x25	PUSH DALI 0-10V 1-10V
1A0172/48	576W	IP20	57x44x25	PUSH CASAMBI

Controller 1 canale - DC
1-channel controller - DC


Rosoni rotondi con driver / Round canopies with driver

3 Sospensioni 3 suspensions	Articolo Item	Finitura Finish	Dimmerazione Dimming
	RS88/02	-BI  -NE  -BV 	ON-OFF PUSH DALI 0-10V
	RS88/03	-BI 	ON-OFF PUSH CASAMBI
		-NE 	
		-BV 	
	RS88/05	-BI 	ON-OFF PUSH DALI 0-10V
		-NE 	
		-BV 	
	RS88/06	-BI 	ON-OFF PUSH CASAMBI
		-NE 	
		-BV 	

Rosoni rettangolari con driver / Square canopies with driver

3 Sospensioni 3 suspensions	Articolo Item	Finitura Finish	Dimmerazione Dimming
	RS58/01	-BI  -NE  -BV 	ON-OFF PUSH DALI 0-10V
	RS58/02	-BI 	ON-OFF PUSH CASAMBI
		-NE 	
		-BV 	
	RS58/11	-BI 	ON-OFF PUSH DALI 0-10V
		-NE 	
		-BV 	
	RS58/12	-BI 	ON-OFF PUSH CASAMBI
		-NE 	
		-BV 	


Rosone con driver + staffa Batacù per decentramento 1pz
Canopy with driver + Batacù bracket for decentralization 1pc



Articolo Item	Finitura Finish	Dimmerazione Dimming
521	-NE	PUSH DALI
composed by		
RS69 (1Pz)		
520 (1Pz)		

Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version


Rosone con driver + staffa Batacù per decentramento 3pz
Canopy with driver + Batacù bracket for decentralization 3pcs




Articolo Item	Finitura Finish	Dimmerazione Dimming
523	-NE	PUSH DALI
composed by		
RS92 (1Pz)		
520 (3Pz)		

Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version

Jack per track 230V + Connettore nero / Jack for track 230V + black connector



Articolo Item	Finitura Finish	Dimmerazione Dimming
211/02	-JBI	ON-OFF
	-JNE	



211/05	-JBI	L-C
	-JNE	

	211/06	-JBI -JNE	DALI
	211/09	-JBI -JNE	CASAMBI

Passacavi / Cable entry

Articolo Item	Finitura Finish
	BEAMKIT01 -NA
	BEAMKIT02 -NA